


# STORM P LED

## Diffuser and Wall Luminaires



**Images for the product family and options:**



**Description:** Surface mounted plastic LED luminaire  
 Light distribution type: direct  
 Optical system: opal polycarbonate diffuser, UV stable, impact resistant  
 Housing: polycarbonate  
 Colour: white, black

**General data:** Mains voltage: 220-240V, 50-60Hz  
 LED lifetime, h: 50000/L70B50  
 SDCM: 5  
 Protection class IEC: II  
 Ingress protection code: IP65  
 Mechanical impact resistance: IK10  
 Operating temperature range, °C: ta -20...+40

**Installation:** On the ceiling or wall. Push-in terminal, 2x2x2.5mm<sup>2</sup>

**Environment:** Indoor/Outdoor with roof

**Application:** Office, education, corridor, staircase, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Storm P LED1x1000/1500/2000/2550 J584 T830/40	352	352	68	1000/1500/2000/2550	10/14/18/22	95/100/100/102	80+	3000/4000	1,4
Storm P LED1x1000/1500/2000/2550 J584 T830/40 BLACK	352	352	68	1000/1500/2000/2550	10/14/18/22	95/100/100/102	80+	3000/4000	1,4

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

\*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

**Available options:**

- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- DALI Driver with DALI interface and switch-control dimming
- COR Driver with Corridor function (never off)
- \*note - for DALI, COR options, indicate what output is required
- MW Integrated microwave (MW) motion sensor with on-off control
- EM3 Emergency version 3 hours
- EM3B Emergency version 3 hours (best available technology)

- EM3A Emergency version equipped with an autonomous testing system, 3 hours
- EM3D Emergency version 3 hours with DALI interface
- \*note - Operating temperature range for Luminaires with EM option, C: ta 0...+35
- EM3Atmin-25 Emergency version equipped with an autonomous testing system, 3 hours. Suitable for low ambient temperatures up to -25 C

**STANDARD**

