




## MEDO® RING 60

pendant light, pendant length 300cm, 3000/4000K, 110°, DALI, touch, black

The best MEDO® of all time is now also available as a pendant light in an elegant design: the MEDO® RING impresses with a longer service life and better energy efficiency of over 120 lm/W. It is available in two sizes and two colours, and can be controlled via trailing edge or DALI. The CCT switch (3000K/4000K) allows the light temperature to be selected as desired.



## TECHNICAL DATA

Item no.	1008589
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	22
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	22
Number of luminaires at LS C16A	36
Level of inrush current	28 A
Duration of inrush current	165 µs
Temperature at glass (light emission)	29 °C
Lumen	3750/4000 lm
Colour temperature	3000/4000 Kelvin
Color	black
CRI	90
UGR ≤	25

<b>Service life</b>	50000 h
<b>Height</b>	7 cm
<b>Diameter</b>	60 cm
<b>Pendant length</b>	300 cm
<b>Net weight</b>	3.85 kg
<b>Gross weight</b>	5.7 kg