


NIGEA LED

Park and Street Luminaires



Description: Ground-mounted LED bollard
 Light distribution: omnidirectional
 Optical system: matt aluminium reflector, clear polycarbonate diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 0/50-60Hz (T840: 220-240V, 50-60Hz)
 LED lifetime, h: 50000/L80B10
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -30...+35

Installation: On the ground (flange mounting plate included). Screw terminal, 3x1x1.5mm²

Environment: Outdoor

Application: Park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output, lm	System power, W	System efficacy, lm/W	CRI	CCT, K	Weight, kg
Nigea LED1x1650 G989 T830	165	165	805	1542	14,3	108	80+	3000	3,5
Nigea LED1x1650 G989 T840	165	165	805	1627	14,3	114	80+	4000	3,5

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification


*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+
 DALI Driver with DALI interface and switch-control dimming
 LOOP LED driver with doubled input terminals for looping the mains cables

RAL RAL colour
 *note - price for uncommon RAL colour could be different from indicated. Ask before placing an order

STANDARD



Available accessories:



Product: Ground MTG KIT - Nigea LED
 Description: Kit for mounting the luminaire to the ground