


# SARGAS LED

## Park and Street Luminaires



**Images for the product family and options:**



**Description:** Pole-mounted LED park luminaire  
 Light distribution type: direct  
 Optical system: lenses, tempered glass diffuser, impact resistant  
 Housing: aluminium  
 Colour: Light grey, RAL 9006

**General data:** Mains voltage: 220-240V, 0/50-60Hz  
 LED lifetime, h: 100000/L90B10  
 SDCM: 5  
 Protection class IEC: I  
 Ingress protection code: IP66  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -40...+40

**Installation:** With two screws on poles Ø60mm. Cable, 3.0m, 3x0.75mm<sup>2</sup>

**Environment:** Outdoor

**Application:** Park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Sargas LED1x5050 J455 T740 LS140	500	500	235	5009	34,3	146	70+	4000	10,0
Sargas LED1x7100 J456 T740 LS140	500	500	235	7073	48,7	145	70+	4000	10,0
Sargas LED1x9700 J457 T740 LS140	500	500	235	9663	68	142	70+	4000	10,0

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. . . . .  
 improving its products. The right is reserved to change any product specifications without prior notification

\*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

**Available options:**

T730 Colour temperature 3000K, CRI 70+  
 T740 Colour temperature 4000K, CRI 70+  
 SHADE Deglaring decorative shade for Sargas LED luminaire  
 DALI Driver with DALI interface and switch-control dimming  
 ADIM Driver with autonomous two-level dimming

PCA Photocell 20mm miniature type, IP65, 35 lux; 1:05 ratio  
 II Electric Shock protection class II  
 RAL RAL colour

\*note - price for uncommon RAL colour could be different from indicated. Ask before placing an order

**LS140**

