


AURIGA P LED

Downlights



Images for the product family and options:



Description: Recessed mounted LED downlight
 Light distribution type: direct
 Optical system: faceted aluminium reflector, 60°/ matt aluminium reflector, 80°, low glare, opal PMMA diffuser
 Housing: aluminium
 Colour: white, RAL9016

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L80B10
 SDCM: 5
 Protection class IEC: II
 Ingress protection code: IP44
 Mechanical impact resistance: IK04
 Operating temperature range, °C: ta 0...+35

Installation: In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm²

Environment: Indoor

Application: Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Auriga P LED1x950 J721 T830/40/57 R60	114	114	66	950	10	95	80+	3000/ 4000/ 5700	0,3
Auriga P LED1x1900 G986 T830/40/57 R60	174	174	87	1900	20	95	80+	3000/ 4000/ 5700	0,4
Auriga P LED1x2550 G987 T830/40/57 R60	232	232	110	2660	28	95	80+	3000/ 4000/ 5700	0,7
Auriga P LED1x3350 J722 T830/40/57 R60	232	232	110	3325	35	95	80+	3000/ 4000/ 5700	0,7
Auriga P LED1x1100 J723 T830/40/57 R80	114	114	66	1100	10	110	80+	3000/ 4000/ 5700	0,3
Auriga P LED1x2400 G986 T830/40/57 R80	174	174	87	2400	20	120	80+	3000/ 4000/ 5700	0,4
Auriga P LED1x3350 G987 T830/40/57 R80	232	232	110	3320	27,9	119	80+	3000/ 4000/ 5700	0,7
Auriga P LED1x4050 J724 T830/40/57 R80	232	232	110	4025	35	115	80+	3000/ 4000/ 5700	0,7



*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C.

improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

DALI EM3A	Driver with DALI interface and switch-control dimming Emergency version equipped with an autonomous testing system, 3 hours	Europlug-1.5m Europlug-3.0m	2-pole "Europlug" type plug with 2x1.0mm ² 1.5m cable 2-pole "Europlug" type plug with 2x1.0mm ² 3.0m cable
EM3D	Emergency version 3 hours with DALI interface	RND BLACK	Round luminaire frame in black
WIE3-0.5m	3-pole "Wieland - gesis classic" type or compatible connector with 0.5m cable	SQ WHITE	Square luminaire frame in white
		SQ BLACK	Square luminaire frame in black
WIE5D-0.5m	5-pole DALI "Wieland - gesis classic" type or compatible connector with 0.5m cable	GLASS WHITE	Round luminaire frame in white, with dropped down glass cover
QBX2-0.1m	2-pole quick connection box on 0.1m cable, Push-in terminal, 2x2x2.5mm ²	GLASS BLACK	Round luminaire frame in black, with dropped down glass cover



Accessories:



Product: Surface MTG BOX Auriga P LED 20W G986 white
 Description: Surface mounting cover for Auriga P LED, white steel, 182x182x155mm
**note - Luminaire with surface mounting cover, protection degree is IP20*



Product: Surface MTG BOX Auriga P LED 20W G986 black
 Description: Surface mounting cover for Auriga P LED, black steel, 182x182x155mm
**note - Luminaire with surface mounting cover, protection degree is IP20*



Product: Surface MTG BOX Auriga P LED 28W G987 white
 Description: Surface mounting cover for Auriga P LED, white steel, 240x240x180mm
**note - Luminaire with surface mounting cover, protection degree is IP20*



Product: Surface MTG BOX Auriga P LED 28W G987 black
 Description: Surface mounting cover for Auriga P LED, black steel, 240x240x180mm
**note - Luminaire with surface mounting cover, protection degree is IP20*