


LEVANTO UGR LED

Recessed Luminaires



Images for the product family and options:



Description: Recessed mounted LED panel
 Light distribution type: direct
 Optical system: micro-prismatic diffuser, UGR<19
 Housing: aluminum
 Colour: white (RAL9016)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L70B50
 SDCM: 5
 Protection class IEC: II
 Ingress protection code: IP40
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+35

Installation: In modular suspended ceilings (600x600 / 1200x300), in ceilings with cut-out openings (mounting accessories to be ordered separately). Push-in terminal, 2x1x1.5mm² (DALI: Push-in terminal, 4x2x2.5mm²)

Environment: Indoor

Application: Office, education, corridor, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI* (Ra)	CCT*, K	Weight, kg
Levanto UGR LED1x3650 G673 T830 MPRZ	595	595	33	3600	36	100	80+	3000	1,8
Levanto UGR LED1x3650 G674 T830 MPRZ	1195	295	33	3600	36	100	80+	3000	1,8
Levanto UGR LED1x3650 G673 T840 MPRZ	595	595	33	3650	36	101	80+	4000	1,8
Levanto UGR LED1x3650 G674 T840 MPRZ	1195	295	33	3650	36	101	80+	4000	1,8
Levanto UGR LED1x3650 G673 T830 MPRZ DALI	595	595	33	3600	36	100	80+	3000	1,8
Levanto UGR LED1x3650 G674 T830 MPRZ DALI	1195	295	33	3600	36	100	80+	3000	1,8
Levanto UGR LED1x3650 G673 T840 MPRZ DALI	595	595	33	3650	36	101	80+	4000	1,8
Levanto UGR LED1x3650 G674 T840 MPRZ DALI	1195	295	33	3650	36	101	80+	4000	1,8
Levanto UGR LED1x4300 G864 T830 MPRZ	595	595	33	4250	36	118	80+	3000	1,8
Levanto UGR LED1x4300 G864 T840 MPRZ	595	595	33	4320	36	120	80+	4000	1,8
Levanto UGR LED1x4300 G864 T830 MPRZ DALI	595	595	33	4250	36	118	80+	3000	1,8
Levanto UGR LED1x4300 G864 T840 MPRZ DALI	595	595	33	4320	36	120	80+	4000	1,8

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C.

improving its products. The right is reserved to change any product specifications without prior notification


*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

DALI Driver with DALI interface and switch-control dimming
 DALI LOOP Driver with DALI interface, switch-control dimming and doubled input terminals for looping the mains cables
 EAIRB-M Master luminaire with integrated smart sensor and driver with Bluetooth communication and grouping possibilities for lighting control
 *note - for EAIRB-M options ingress protection IP20
 EAIRB-S Slave luminaire with integrated EAIR type driver for lighting control
 *note - max system size 1x EAIR-M + 3x EAIR-S.
 *note - max wire length from EAIR-M to last EAIR-S - 11m.
 EM3A Emergency version equipped with an autonomous testing system, 3 hours

EM3D Emergency version 3 hours with DALI interface
 *note - EM3A, EM3D options are not applicable with surface mounting accessories
 WIE3-0.5m 3-pole "Wieland - gesis classic" type or compatible connector with 0.5m cable
 WIE5D-0.5m 5-pole DALI "Wieland - gesis classic" type or compatible connector with 0.5m cable
 Europlug-1.5m 2-pole "Europlug" type plug with 1.5m cable
 Europlug-3.0m 2-pole "Europlug" type plug with 3.0m cable
 QBX2-0.1m 2-pole quick connection box on 0.1m cable, Push-in terminal, 2x2x2.5mm²
 IP44 IP44 protection degree
 T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+

MPRZ



Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003/
Recessed MTG FRAME S326x1226 RAL9003
Description: Frame for LED luminaire 595x595mm
installation into plasterboard ceiling (1pcs), white steel/
Frame for LED luminaire 1195x295mm installation into
plasterboard ceiling (1pcs), white steel



Product: Surface MTG BOX S606x606x70 Levanto
PLN/UGR LED v2 RAL9003/Surface MTG BOX
S1206x306x70 Levanto PLN/UGR LED v2/Calima R LED
RAL9003

Description: Surface mounting box for LED panel
595x595mm (1pcs), white steel/ Surface mounting box for
LED panel 1206x306mm (1pcs), white steel
**note - surface mounting box is compatible with EM3 option*



Product: Decorative COVER 595x595/D500 Levanto
PLN/UGR LED RAL9003
Description: Decorative cover with 500mm round opening
for LED panel 595x595mm (1pcs), white steel



Product: Suspension MTG kit Levanto UGR/PLN G series
Description: Suspension kit for LED panel



Product: Decorative REFLECTOR 595x595 Levanto
PLN/UGR LED RAL9003
Description: Decorative reflector for LED panel
595x595mm (1pcs), white steel



Product: Surface MTG kit Levanto UGR/PLN G2 series
S600x600 RAL9016
Description: Surface mounting kit for recessed LED
luminaires 600x600mm (1pcs), white extruded aluminium



Product: Surface MTG kit Levanto UGR/PLN G2 series
S300x1200 RAL9016
Description: Surface mounting kit for recessed LED
luminaires 300x1200mm (1pcs), white extruded aluminium



Product: Recessed MTG kit LEVANTO PLN G series
Description: Recessed MTG kit



Product: Decorative BORDER 595x595 Levanto
PLN/UGR LED RAL9003
Description: Decorative perforated reflector for LED panel
595x595mm (1pcs), white steel

Applications:

